

Line measurement

Customer:

Date/place:

Inspector:

Model/Size: rev3

Serial-Nr.

Date of manufactory

Riser:

Steering lines

Tolerance:



Riser length				
A1	A2	B	C	D

Area cm		
Span	Cord	

Note:

Pull force

A level			
measure	nominal	Dif-A	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16	7080	-7080	
15	7145	-7145	
14	7225	-7225	
13	7305	-7305	
12	7445	-7445	
11	7465	-7465	
10	7560	-7560	
9	7630	-7630	
8	7770	-7770	
7	7765	-7765	
6	7845	-7845	
5	7890	-7890	
4	7980	-7980	
3	7955	-7955	
2	7990	-7990	
1	8040	-8040	
1	8040	-8040	
2	7990	-7990	
3	7955	-7955	
4	7980	-7980	
5	7890	-7890	
6	7845	-7845	
7	7765	-7765	
8	7770	-7770	
9	7630	-7630	
10	7560	-7560	
11	7465	-7465	
12	7445	-7445	
13	7305	-7305	
14	7225	-7225	
15	7145	-7145	
16	7080	-7080	
17			
18			
19			
20			
21			
22			
23			
24 L			

B level			
measure	nominal	Dif-B	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16	7085	-7085	
15	7135	-7135	
14	7215	-7215	
13	7275	-7275	
12	7415	-7415	
11	7430	-7430	
10	7520	-7520	
9	7585	-7585	
8	7725	-7725	
7	7715	-7715	
6	7785	-7785	
5	7835	-7835	
4	7920	-7920	
3	7890	-7890	
2	7925	-7925	
1	7975	-7975	
1	7975	-7975	
2	7925	-7925	
3	7890	-7890	
4	7920	-7920	
5	7835	-7835	
6	7785	-7785	
7	7715	-7715	
8	7725	-7725	
9	7585	-7585	
10	7520	-7520	
11	7430	-7430	
12	7415	-7415	
13	7275	-7275	
14	7215	-7215	
15	7135	-7135	
16	7085	-7085	
17			
18			
19			
20			
21			
22			
23			
24 L			

C level			
measure	nominal	Dif-C	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16	7145	-7145	
15	7205	-7205	
14	7290	-7290	
13	7355	-7355	
12	7480	-7480	
11	7500	-7500	
10	7605	-7605	
9	7675	-7675	
8	7795	-7795	
7	7795	-7795	
6	7865	-7865	
5	7915	-7915	
4	8005	-8005	
3	7980	-7980	
2	8015	-8015	
1	8065	-8065	
1	8065	-8065	
2	8015	-8015	
3	7980	-7980	
4	8005	-8005	
5	7915	-7915	
6	7865	-7865	
7	7795	-7795	
8	7795	-7795	
9	7675	-7675	
10	7605	-7605	
11	7500	-7500	
12	7480	-7480	
13	7355	-7355	
14	7290	-7290	
15	7205	-7205	
16	7145	-7145	
17			
18			
19			
20			
21			
22			
23			
24 L			

D level			
measure	nominal	Dif-D	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16			
15			
14			
13			
12			
11			
10			
9			
8			
7			
6	8105	-8105	
5	8090	-8090	
4	8145	-8145	
3	8125	-8125	
2	8175	-8175	
1	8280	-8280	
1	8280	-8280	
2	8175	-8175	
3	8125	-8125	
4	8145	-8145	
5	8090	-8090	
6	8105	-8105	
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24 L			

E level			
measure	nominal	Dif-E	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16			
15			
14			
13			
12			
11			
10			
9			
8			
7			
6			
5			
4			
3			
2			
1			
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24 L			

Brake Lines			
measure	nominal	Dif-BL	Sy
24 R			
23			
22			
21			
20			
19			
18			
17			
16			
15			
14			
13			
12			
11			
10			
9	7400	-7400	
8	7345	-7345	
7	7355	-7355	
6	7415	-7415	
5	7570	-7570	
4	7700	-7700	
3	7865	-7865	
2	8085	-8085	
1	8420	-8420	
1	8420	-8420	
2	8085	-8085	
3	7865	-7865	
4	7700	-7700	
5	7570	-7570	
6	7415	-7415	
7	7355	-7355	
8	7345	-7345	
9	7400	-7400	
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24 L			

XB32L rev3 - Rise4/SOAR L										
Linked Line Check Sheet										
	A		B		C		D		K	
	Name		Name		Name		Name		Name	
1	A1	8040	B1	7975	C1	8065	D1	8280	K1	8420
2	A2	7990	B2	7925	C2	8015	D2	8175	K2	8085
3	A3	7955	B3	7890	C3	7980	D3	8125	K3	7865
4	A4	7980	B4	7920	C4	8005	D4	8145	K4	7700
5	A5	7890	B5	7835	C5	7915	D5	8090	K5	7570
6	A6	7845	B6	7785	C6	7865	D6	8105	K6	7415
7	A7	7765	B7	7715	C7	7795			K7	7355
8	A8	7770	B8	7725	C8	7795			K8	7345
9	A9	7630	B9	7585	C9	7675			K9	7400
10	A10	7560	B10	7520	C10	7605				
11	A11	7465	B11	7430	C11	7500				
12	A12	7445	B12	7415	C12	7480				
13	A13	7305	B13	7275	C13	7355				
14	A14	7225	B14	7215	C14	7290				
15	A15	7145	B15	7135	C15	7205				
16	A16	7080	B16	7085	C16	7145				
K* - K-lines measured including the length of raff-webbing										

XB32L rev3 - Rise4/SOAR L			
8000/U-090 --- 2 8000 090 222 0 red			
Name	No.	Length	
B10	2	520	
B12	2	525	
B11	2	540	
A12	2	555	
A10	2	560	
A11	2	575	
B9	2	585	
B2	2	625	
A9	2	630	
B3	2	640	
B4, B6	4	670	
B1, B7	4	675	
B8	2	685	
A2	2	690	
A3	2	705	
B5	2	720	
A7	2	725	
A4, A6, A8	6	730	
A1	2	740	
A5	2	775	
K6	2	1345	
K5, K8	4	1475	
K7	2	1485	
K4	2	1500	
K9	2	1530	
K3	2	1645	
K2	2	1660	
K1	2	1995	
8000/U-070 --- 2 8000 070 222 0 red			
Name	No.	Length	
A16	2	460	
B16	2	465	
B14	2	490	
A14	2	500	
B15	2	515	
A15, C16	4	525	
B13	2	550	
C14	2	565	
A13	2	580	
C15	2	585	
C12	2	590	
C10	2	605	
C11	2	610	
C13	2	630	
C9	2	675	
C6	2	750	
C7, C8	4	755	
C5	2	800	
C2	2	875	
C3	2	895	
C4	2	920	

C1	2	925		
D3	2	985		
D4, D5	4	1005		
D6	2	1020		
D2	2	1035		
D1	2	1140		
1ABC8	6	1305		
1ABC7	6	1410		
8000/U-190 --- 2 8000 190 222 0 red				
Name	No.	Length	INI	
2K1, 2K2	4	1610	both sides	
1A2	2	1880	both sides	
1A1	2	1930	both sides	
1A3	2	1955	both sides	
AR3	2	5210	top side	red sleeve lower side
BR3	2	5210	top side	blue sleeve lower side
CR3	2	5210	top side	green sleeve lower side
8000/U-130 --- 2 8000 130 222 0 red				
Name	No.	Length	INI	
1ABC6	6	1140	both sides	
1ABC5	6	1250	both sides	
1K4	2	1305	both sides	
1K3	2	1505	both sides	
1K2	2	1610	both sides	
1C2	2	1715	both sides	
1C1	2	1770	both sides	
1K1	2	1815	both sides	
1ABC4, 1B2	8	1880	both sides	
1B1	2	1930	both sides	
1BC3	4	1955	both sides	
8000/U-280 --- 2 8000 280 222 0 red				
Name	No.	Length	INI	
AR1	2	4830	top side	red sleeve lower side
8000/U-230 --- 2 8000 230 222 0 red				
Name	No.	Length	INI	
AR2	2	4620	top side	red sleeve lower side
BR2	2	4620	top side	blue sleeve lower side
CR2	2	4620	top side	green sleeve lower side
BR1	2	4830	top side	blue sleeve lower side
CR1	2	4830	top side	green sleeve lower side
8000/U-130 --- 2 8000 130 002 0 grey				
Name	No.	Length	INI	
BR4	2	4775	top side	green sleeve lower side
PPSL200 - yellow				
Name	No.	Length		
KR1	2	2970		sleeve lower side